

Small for great comfort.



TS Slimline | The electrothermal actuator

www.eberle.de

EBERLE

Application and function

The new TS Slimline electrothermal actuators are the logical further development of the proven and reliable TS actuators. Now significantly smaller in size, the TS Slimline has the same technical features with the usual high quality standard.

- Ideal for heating circuit manifolds with a small (up to at least 40 mm) distance between the valves
- Robust and noiseless
- Indication of stroke position via window
- Suitable for all valves M 30 x 1.5 mm
- 230 V and 24 V versions
- Very good price-performance ratio



Technical data:

Type	Slimline	
Item number	0496 1001 1015	0497 1001 1015
Power supply	230 V~ 50 Hz	24 V AC/DC
Switch-on current	< 1 A	
Power consumption	2.5 W	
Thermal actuator	open / closed	
Valve type	de-energised closed	
Connection cable	2 x 0,5 mm ² , 100 cm long (optionally any cable length), free cable end with	
Protection type/ protection class	IP44 in vertical position / II	
Stroke	3.5 mm	
Connection dimension	M 30 x 1.5 mm	
Dimensions	39 x 54 x 88 mm (B x L x H)	
Storage temperature	-25...70° C	
Operating temperature	0...50° C	
Closing force	90 N	

Dimensions

